

# TECHNICAL SHEET

SIATA  
COMMERCIAL VALVE V230





## SIATA COMMERCIAL VALVE V230

### TECHNICAL CHARACTERISTICS

- Flow rate: up to 8.5 m<sup>3</sup>/h
- Quick connect clips allowing easy installation and maintenance
- Hydraulically actuated
- Internal turbine option for meter control
- Driver replica of the pressure point for any special applications, such as driving an external brine valve or closing the valve outlet
- Suitable for simplex, duplex or multiplex softening systems, as well as for filtration, demineralisation, dealkalisation or iron & manganese removal applications
- Compatible with the entire Siata controller range



### VALVE SPECIFICATION

Material	Glassfiber reinforced ABS
Color	Blue or black
Hydrostatic pressure	22 bar
Working pressure	1.5-6 bar
Working temperature	5-40°C

### FLOW RATE (3.5 BAR INLET - VALVE ALONE)

Continuous ( $\Delta p = 1$ bar)	8.5 m <sup>3</sup> /h
Peak ( $\Delta p = 1.9$ bar)	11 m <sup>3</sup> /h
Cv*	9.6 gpm
Maximum backwash ( $\Delta p = 1.9$ bar)	4 m <sup>3</sup> /h
Maximum rapid rinse ( $\Delta p = 1.9$ bar)	4.5 m <sup>3</sup> /h

\* Cv: Flow rate of valve alone in gpm at 0.07 bar pressure drop.

### DOWN FLOW REGENERATION

Adjustable cycles	Depending on controller fitted
-------------------	--------------------------------

## VALVE CONNECTIONS

Inlet/Outlet	male 2 inches BSP threaded
Distributor pipe	DN 40
Drain line	20 mm - QC**
Brine line	3/8 inch BSP
Mounting base	4 inches BSP threaded
Height (from top of tank)	129 mm ± 2

\*\*QC: Quick connect

## TANK SIZE APPLICATION (RECOMMENDED)

Water softener	8 - 21 inches (max 300 L of resin)
Filter	8 - 21 inches (according to filter media specs)
Demineralisation	8 - 21 inches (max 300 L of resin)

## METER

### Internal

Accuracy range (± 5%)	12 - 200 Lpm
-----------------------	--------------

### External

Accuracy range 3/4 inch (± 5%)	10 - 120 Lpm
Accuracy range 1 1/2 inch (± 5%)	12 - 200 Lpm

## REGENERATION CYCLES

Softener & Demineralisation	<ol style="list-style-type: none"> <li>1) Backwash (Upflow)</li> <li>2) Brine &amp; slow rinse (Down flow)</li> <li>3) Rapid rinse (Down flow)</li> </ol>
Filter***	<ol style="list-style-type: none"> <li>1) Backwash (Upflow)</li> <li>2) Rapid rinse (Down flow)</li> </ol>

\*\*\* Depending on the controller type brine draw and slow rinse time must be set on 0.

## OPTIONS

Remote Bypass w/ or w/o sample tap	yes
Driver replica	yes

[www.pentairaquaeurope.com](http://www.pentairaquaeurope.com)