Clack Mineral Tanks



Colors: Blue, Natural, Black, Almond & Grey

MADE IN USA

Clack Mineral Tanks are made to ensure reliable performance for many years. The fiberglass filament winding covers a high performance composite high density polyethylene (HDPE) liner. The design provides a continuous seamless inner liner with a glass filled polypropylene inlet for higher strength and pressure capabilities. Tanks are available from 8" to 24" diameter, 2.5"and 4”- 8 NPSM top opening.

FEATURES:

- For water softener/filtration applications
- 5 year warranty for 8”-24” vessels

MATERIAL OF CONSTRUCTION:

- Inner liner high density polyethylene
- Threaded inlet glass filled polypropylene

OPERATING PARAMETERS:

- Maximum operating pressure: 150 psi (10.34 bars)
- Maximum operating temperature: 120°F (48.8°C)

NSF

Certified to NSF/ANSI 61

CLACK DESIGN PARAMETERS:

- Safety factor: 4:1
- Minimum burst at 600 psi (41.36 bars)
- Tested to 100,000 cycles / 0-150 psi without leakage

NSF DESIGN PARAMETERS:

- Safety factor: 4:1
- Minimum burst at 600 psi (41.36 bars)
- Tested to 100,000 cycles / 0-150 psi without leakage

Tank Size (Inches)	Top Opening (Inches)	Qty per Bulk Pack
8 x 35*	2.5	18
8 x 40	2.5	18
8 x 44	2.5	18
9 x 35*	2.5	16
9 x 40	2.5	16
9 x 48	2.5	16
10 x 35*	2.5	16
10 x 40	2.5	16
10 x 44	2.5	16
10 x 47	2.5	16
10 x 54	2.5	16
12 x 48	2.5	9
12 x 52	2.5	9
13 x 54	2.5	9
14 x 65**	4	1
16 x 65**	4	1
18 x 65**	4	1
21 x 62**	4	1
24 x 72**	4	1

*Available with or without base
**Please check for availability